

Sustainable Hydropower – Design & Operation


Christopher Grant

Oslo

4th September 2017




Mekong mainstream – planned projects



Planned upper cascade comprises:

- 5 projects commanding the available reach;
- Gross heads in the range 20 to 30 m;
- Creating reservoirs, largely within bank up to 100 km long



Mekong mainstream – key vulnerabilities

• Fish:



- zero flow velocity prevents the downstream drift of eggs and larvae - breaking the migration cycle.
- downstream fish mortality in turbines and undershot spillway gates

• Sediment:

- reservoirs trap coarse sands and gravels
- sand can be mobilised by flushing but this severely impacts ecology




• Water quality:

- increased temperature
- discharge of algae
- decreased oxygen in early years




Mekong mainstream – alternative concepts

- Natural bypass:
 - Don Sahong commands one channel at Kone Falls
 - A lower Sambor alternative with preserve a left bank by pass channel



- Sub divided projects:

- Lower heads
- Smaller reservoirs
- Ability to restore natural river conditions and 100% connectivity




Mekong Mainstream – sector gate barrage




Nakdong Dalseong – S Korea




Yeosu – S Korea




GENERATION



SPILLING



SCOURING



SHUT DOWN





Mekong Mainstream – sector gate barrage

Comparison with a single scheme

- Construction cost:
 - Design comparison currently in progress, but early indications suggest <+45%




- Finance cost:
 - Preliminary modelling suggests -30% if projects are constructed concurrently

- Energy impact
 - Tailwater impact -7%
 - 3 month shut down -30%



Mekong tributaries – seasonal storage

- Storage projects on the tributaries introduce loss of seasonality and floods in downstream discharges





- Tonle Sap – one of the worlds most productive eco systems



Mekong tributaries – storage projects

- Single storage:
 - operated to deliver dry season energy and capture wet season floods
 - partial seasonality in discharge could be restored by taking less dry season energy
- Cascade storage:
 - the downstream project in a cascade does not need its seasonal storage
 - keeping the reservoir full provides a higher average head and restores seasonal floods



PPA Implications

- If owners are paid for energy it creates an incentive to resist environmental objectives:
 - seasonal regulation
 - minimise compensation & fish by-pass flows
 - project (not river basin) optimisation
 - all environmental constraints must be defined before the project proceeds

- If owners were paid for available power, a central river basin authority could direct operations:
 - integrated river basin optimisation
 - plant can be despatched to suit system requirements
 - improved cascade management
 - multi criteria (non financial) decision making
 - adaptive environmental management for fish, water quality and sediment



Contact details

Christopher Grant

Multiconsult UK Ltd
International House
Dover Place
Ashford, Kent
United Kingdom

Tel +44 7880 406216

chris.grant@multiconsultgroup.com

www.multiconsultgroup.com

